		2011/05/25 : CIA-RDP8	32-00457R010600270001-8 REPORT	50X1-HUM
	INFORMATIO	on report	CD NO.	
COUNTRY	Germany (Russian Zone)		DATE DISTR. 13 March	1952
SUBJECT	Shipbuilding Plans of the Warnot Shippards	and Neptun	NO. OF PAGES 1	
PLACE ACQUIRED			NO. OF ENCLS.	
DATE OF INFO.			SUPPLEMENT TO REPORT	50X1-HUM
THIS DOCUMENT OF THE UNITED AND 704, OF THE AND 104, OF THE AND 105 INS.	CONTAINS INFO: LEWICH AFFECTING THE NATIONAL DEFENSE TOTATES, WITHIN THE MILAMING OF WILE 13, SECTIONS 703 EU. S. CODE, AS AMERDED. 175 THANDSHISSION OF REPORT OF MECHANISM OF THAN STANDARD CREATER OF THE STANDARD CREATER	THIS IS UNE	VALUATED INFORMATION	50X1-HUM
1.	It is intended that the Warnow cargo ships for the DDR Merchan are being carried out on sunker Prussian Service, which have be ships, upon completion, will pras excursion boats for Russian	t Fleet ships, preven raised and towed	lously belonging to the in. It is planned that Sea where they will be	pairs East t these used
2.	of these vessels, which are almost complete, confirm their intended use. The ways in Warneminde which are parallel to the water must be increased in length to accommodate the keels of the planned ships. It is planned to build four different types of vessels at the Warnow shipyards. The engines are to be housed in the stern of each type of ship and it has been calculated that engines of one HP per gross registered ton of ship will be required. A standard type of ship engine has been designed and is under construction in the SAG Buckau-Wolf, Magdeburg. Should the size of the cargo vessels prove too large for one of these standard engines, it is intended that two, or perhaps more, be coupled together. The design of the coupling machinery is not yet satisfactory and experiments are at present being conducted to improve it.			
3.	The large type of ship whose construction is planned in the Warnov yards will weigh approximately 9,500 tons. Such a ship will have a draft of approximately 28 feet. At the present time, the depth of water in the main shipping channel between Warneminde and Rostock is only 18 feet. To make the channel navigable for the larger ships dredging operations must increase the depth by at least another 11 feet. At present dredging operations are in progress, but the depth which has so far been attained in Warneminde is approximately 8 feet short of the required target because the foundations of the pier have not been sunk deeply enough into firm ground. It is expected that the eastern pier of Warneminde would crumble if dredging increased the depth of the water to 22 feet.			
<u>1</u> .	To dredge safely to a depth of 29 feet, the whole pier and its installations would have to be moved farther to the east. A conservative estimate of the cost of this work is 3,000,000 DM. At the present time, this amount of money cannot be allocated.			
5.	The Neptunwerft in Rostock has to a depth of 29 feet as it all time, the Neptunwerft is used	only for the repair	Wild coreo Academa	•
STATE		DISTRIBUTION		
ARMY	X AIR X FBI			
	l and			
		Document No.		
		No Change In Declassifie		
	· · · · · · · · · · · · · · · · · · ·	Cia:s. Change		
		Auth.: HR 7)-2	
•		Date: 5 SEF	1978	50X1_HUM

Sanitized Copy Approved for Release 2011/05/25 : CIA-RDP82-00457R010600270001-8